



DUO-SPOT MODULE

The Duo-spot module is a rectangular panel equipped with two adjustable LED spots. The spots can be individually directed. When the spot is directed downwards, it can also be pushed upwards into the fixture opening so that it does not protrude beyond the frame.

- Easy installation with magnetic mounting
- Two individually adjustable spots with a 300mm spacing
- Available in matte black or matte white finish

Categories: [Refurbishment and Retrofit Fixtures](#)



The Duo-spot module is a rectangular panel equipped with two adjustable LED spots. The spots can be individually directed. When the spot is directed downwards, it can also be pushed upwards into the fixture opening so that it does not protrude beyond the frame.

- Easy installation with magnetic mounting
- Two individually adjustable spots with a 300mm spacing
- Available in matte black or matte white finish

NOTES

ADDITIONAL INFORMATION

Driver positie	Loose driver
Light control	1-10V dimming, Casambi dimming, DALI dimming
Oriëntatie	Down
Shape	Rectangular
Isolatieklasse	Class II
Photobiological safety	IEC 62471: RG1 (low risc)
Optics	Lens
Ambient temperature	-20°C / +40°C
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Productkleur	On request
Bevestiging	Recessed
Kleurtemperatuur	2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI97
Producttoepassing	Education, Hospitality, Office, Public spaces
Kleurconsistentie (SDCM)	SDCM=2
Voltage / frequency	220-240V, 50 / 60Hz
Powerfactor	>0.9
Material	Acrylic, Steel

