



DUO-SPOT MODULE

The Duo-spot module is a rectangular panel equipped with two adjustable LED spots. The spots can be individually directed. When the spot is directed downwards, it can also be pushed upwards into the fixture opening so that it does not protrude beyond the frame.

- Easy installation with magnetic mounting
- Two individually adjustable spots with a 300mm spacing
- Available in matte black or matte white finish

Downloads

[Photometrics Oxo 35 White](#)

Categories: [Refurbishment and Retrofit Fixtures](#)



The Duo-spot module is a rectangular panel equipped with two adjustable LED spots. The spots can be individually directed. When the spot is directed downwards, it can also be pushed upwards into the fixture opening so that it does not protrude beyond the frame.

- Easy installation with magnetic mounting
- Two individually adjustable spots with a 300mm spacing
- Available in matte black or matte white finish

Downloads

[Photometrics Oxo 35 White](#)

NOTES

ADDITIONAL INFORMATION

Air extraction	Optional
Armaturefficiëntie	>140lm/W, >70lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Loose driver
Energielabel	A++
Family	Oxo
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	N/A
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=2
Kleurtemperatuur	2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI97
Lichtbundel (FWHM)	15°, 17°, 24°, 40°
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	Optioneel
Material	Acrylic, Aluminium, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens
Oriëntatie	Adjustable, Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Spot bundle (FWHM)	15°, 17°, 24°, 40°

Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Rectangular
Zelfklevende stofkap	Optioneel

