



## **DUO-SPOT MODULE**

The Duo-spot module is a rectangular panel equipped with two adjustable LED spots. The spots can be individually directed. When the spot is directed downwards, it can also be pushed upwards into the fixture opening so that it does not protrude beyond the frame.

- Easy installation with magnetic mounting
- Two individually adjustable spots with a 300mm spacing
- Available in matte black or matte white finish

**Categories:** [Refurbishment and Retrofit Fixtures](#)



The Duo-spot module is a rectangular panel equipped with two adjustable LED spots. The spots can be individually directed. When the spot is directed downwards, it can also be pushed upwards into the fixture opening so that it does not protrude beyond the frame.

- Easy installation with magnetic mounting
- Two individually adjustable spots with a 300mm spacing
- Available in matte black or matte white finish

**NOTES**

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Air extraction</b>	Optional
<b>Armaturefficiëntie</b>	>140lm/W, >70lm/W
<b>Bevestiging</b>	Recessed
<b>CIE Flux code</b>	93 100 100 100 100
<b>Driver positie</b>	Loose driver
<b>Energielabel</b>	A++
<b>Family</b>	Oxo
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Glare (UGR)</b>	N/A
<b>IP-class</b>	IP20 (upwards)/IP40 (downwards)
<b>Isolatieklasse</b>	Class II
<b>Kleurconsistentie (SDCM)</b>	SDCM=2
<b>Kleurtemperatuur</b>	2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI97
<b>Lichtbundel (FWHM)</b>	15°, 17°, 24°, 40°
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Luchtafzuiging</b>	Optioneel
<b>Material</b>	Acrylic, Aluminium, Steel
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Lens
<b>Oriëntatie</b>	Adjustable, Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
<b>Productkleur</b>	On request
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces
<b>Self-adhesive dust cover</b>	Optional
<b>Spot bundle (FWHM)</b>	15°, 17°, 24°, 40°

<b>Verpakkingsafmetingen</b>	Bulkverpakking
<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)
<b>Voltage / frequentie</b>	220-240V, 50 / 60Hz
<b>Shape</b>	Rectangular
<b>Zelfklevende stofkap</b>	Optioneel

## LDT / PHOTOMETRICS DOWNLOADS

### LDT / Photometrics downloads

All downloads can be found centrally per family at

<https://atomis.nl/ldt-photometrics/>