



EVOLO-L

Evolu-L is an elegant, slim LED fixture featuring a row of mid-power LEDs, each with its own lens and louver. This fixture is specifically designed for use in linear panel ceilings.

- Elegant, slim linear fixture for linear panel ceilings.
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in matte white or matte black textured coating





Downloads

[Photometrics Evolo](#)

Categories: [Baffle luminaires](#)



PRODUCT IMAGES



Evolo-L is an elegant, slim LED fixture featuring a row of mid-power LEDs, each with its own lens and louvre. This fixture is specifically designed for use in linear panel ceilings.

- Elegant, slim linear fixture for linear panel ceilings.
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in matte white or matte black textured coating

Downloads

[Photometrics Evolo](#)

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
Armaturefficiëntie	>130lm/W
Bevestiging	ceiling mounting
CIE Flux code	93 100 100 100 100
Driver positie	Attached to the fixture, Loose driver
Energielabel	A++
Family	Evolo
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI97, CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens en louver
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)

Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Rectangular
Zelfklevende stofkap	Optioneel

