



EVOLO-S BLACK


Evollo-S black, an elegant slim LED pendant fixture featuring a row of mid-power LEDs, each with an individual lens and louver. The fixture creates a light distribution with low glare< making it suitable for office environments. The fixture is made of steel and finished with a decorative textured powder coating in matte black.

- Elegant 36 mm wide slim design
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in a decorative matte black textured coating

Categories: [Pendant luminaires](#)



PRODUCT IMAGES



Evolvo-S black, an elegant slim LED pendant fixture featuring a row of mid-power LEDs, each with an individual lens and louver. The fixture creates a light distribution with low glare< making it suitable for office environments. The fixture is made of steel and finished with a decorative textured powder coating in matte black.

- Elegant 36 mm wide slim design
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in a decorative matte black textured coating

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
Armaturefficiëntie	>140lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Loose driver
Energielabel	A++
Family	Evolu
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens en louver
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	On request, Kabel, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz

Shape	Rectangular
Zelfklevende stofkap	Optioneel

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at
<https://atomis.nl/ldt-photometrics/>