



EVOL-O-S WHITE

Evol-o-S white is an elegantly slim LED pendant luminaire featuring a row of mid-power LEDs, each with an individual lens and louver. The luminaire provides low-glare light distribution< making it ideal for office environments. Constructed from steel, it is finished with a decorative textured powder coating in matte white.

- Elegant 36 mm wide slim design
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in matte white or matte black textured coating


Downloads

[Photometrics Evolo-S](#)

Categories: [Pendant luminaires](#)



PRODUCT IMAGES



Evolu-S white is an elegantly slim LED pendant luminaire featuring a row of mid-power LEDs, each with an individual lens and louver. The luminaire provides low-glare light distribution< making it ideal for office environments. Constructed from steel, it is finished with a decorative textured powder coating in matte white.

- Elegant 36 mm wide slim design
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in matte white or matte black textured coating

Downloads

[Photometrics Evolo-S](#)

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
Armaturefficiëntie	>140lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Integrated
Energielabel	A++
Family	Evolu
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens en louver
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	On request, Kabel, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces, Retail
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz

Shape

Rectangular

Zelfklevende stofkap

Optioneel

