



## **FERRO ROUND 360**

The **Ferro Round 360** is a modern, high-quality **surface-mounted LED fixture** designed for projects where functionality, reliability, and a sleek minimalist design converge. Thanks to its round shape and high-quality PMMA optics, this fixture integrates seamlessly into modern interiors in offices, commercial spaces, public buildings, and utility projects.

- **DALI dimming**
- Motion sensors
- Wireless control options. This makes the Ferro Round 360 suitable for energy-efficient and smart-building solutions
- IP40 (for dry indoor spaces)
- **Diffuser impact resistance:** IK05 for PMMA
- **Dimensions:** Ø 360 mm, height 70 mm

**Categories:** [Surface-mounted luminaires](#)



The **Ferro Round 360** is a modern, high-quality **surface-mounted LED fixture** designed for projects where functionality, reliability, and a sleek minimalist design converge. Thanks to its round shape and high-quality PMMA optics, this fixture integrates seamlessly into modern interiors in offices, commercial spaces, public buildings, and utility projects.

- **DALI dimming**
- Motion sensors
- Wireless control options. This makes the Ferro Round 360 suitable for energy-efficient and smart-building solutions
- IP40 (for dry indoor spaces)
- **Diffuser impact resistance:** IK05 for PMMA
- **Dimensions:** Ø 360 mm, height 70 mm

**NOTES**

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Air extraction</b>	N/A
<b>Armaturefficiëntie</b>	135 lm/W
<b>Bevestiging</b>	Surface-mounted
<b>CIE Flux code</b>	93 100 100 100 100
<b>Driver positie</b>	Integrated
<b>Energielabel</b>	A++
<b>Family</b>	Ferro
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Glare (UGR)</b>	N/A
<b>IK class</b>	IK05
<b>IP-class</b>	IP66
<b>Isolatieklasse</b>	Class II, Class-I
<b>Kleurconsistentie (SDCM)</b>	SDCM=3
<b>Kleurtemperatuur</b>	Tunable White, 2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI90, CRI80
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Luchtafzuiging</b>	n.v.t.
<b>Material</b>	Acrylic, Aluminium
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Opalen diffusor, Reflector
<b>Oriëntatie</b>	Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	On request, Kabel, On the driver
<b>Productkleur</b>	Grey, White
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces, Retail
<b>Self-adhesive dust cover</b>	N/A
<b>Verpakkingsafmetingen</b>	Bulkverpakking
<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)

<b>Voltage / frequentie</b>	220-240V, 50 / 60Hz
<b>Shape</b>	Round
<b>Zelfklevende stofkap</b>	Optioneel

