



FUSION-B

Fusion-B is an LED fixture with modular dimensions for use in strip grid ceilings. These modules are developed as an alternative to T8 and T5 fluorescent fixtures for use in both renovation and new construction projects.

- Suitable for use in combination with all common strip grid ceilings
- Architectural appearance
- Equipped with a prismatic lens (UGR < 19) or an opal diffuser<

Downloads

[Photometrics Fusion-B](#)

Categories: [Strip grid fixtures](#)



Fusion-B is an LED fixture with modular dimensions for use in strip grid ceilings. These modules are developed as an alternative to T8 and T5 fluorescent fixtures for use in both renovation and new construction projects.

- Suitable for use in combination with all common strip grid ceilings
- Architectural appearance
- Equipped with a prismatic lens (UGR < 19) or an opal diffuser<

Downloads

[Photometrics Fusion-B](#)

NOTES

ADDITIONAL INFORMATION

Air extraction	Optional
Armaturefficiëntie	>140lm/W
Bevestiging	ceiling mounting
CIE Flux code	93 100 100 100 100
Driver positie	Attached to the fixture, Loose driver
Energielabel	A++
Family	Fusion
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	Optioneel
Material	Acrylic, Aluminium, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Microprismatic lens, Opalen diffusor
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)

Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Rectangular
Zelfklevende stofkap	Optioneel

PHOTOMETRIC DATA

19.830-P Fusion-B 3S 16W 2100lm 3000K CRI80 G7 (optic 90x845mm)
19.830-P Fusion-B 3S 19W 2400lm 3000K CRI80 G7 (optic 90x845mm)
19.830-P Fusion-B 3S 22W 2750lm 3000K CRI80 G7 (optic 90x845mm)
19.830-P Fusion-B 3S 24W 3050lm 3000K CRI80 G7 (optic 90x845mm)
19.830-P Fusion-B 3S 29W 3550lm 3000K CRI80 G7 (optic 90x845mm)
19.840-P Fusion-B 3S 16W 2250lm 4000K CRI80 G7 (optic 90x845mm)
19.840-P Fusion-B 3S 19W 2600lm 4000K CRI80 G7 (optic 90x845mm)
19.840-P Fusion-B 3S 22W 2950lm 4000K CRI80 G7 (optic 90x845mm)
19.840-P Fusion-B 3S 24W 3300lm 4000K CRI80 G7 (optic 90x845mm)
19.840-P Fusion-B 3S 29W 3850lm 4000K CRI80 G7 (optic 90x845mm)

19.830-P Fusion-B 4S 16W 2100lm 3000K CRI80 G7 (optic 90x1125mm)
19.830-P Fusion-B 4S 18W 2450lm 3000K CRI80 G7 (optic 90x1125mm)
19.830-P Fusion-B 4S 21W 2750lm 3000K CRI80 G7 (optic 90x1125mm)
19.830-P Fusion-B 4S 24W 3100lm 3000K CRI80 G7 (optic 90x1125mm)
19.830-P Fusion-B 4S 28W 3600lm 3000K CRI80 G7 (optic 90x1125mm)
19.840-P Fusion-B 4S 16W 2250lm 4000K CRI80 G7 (optic 90x1125mm)
19.840-P Fusion-B 4S 18W 2650lm 4000K CRI80 G7 (optic 90x1125mm)
19.840-P Fusion-B 4S 21W 3000lm 4000K CRI80 G7 (optic 90x1125mm)
19.840-P Fusion-B 4S 24W 3350lm 4000K CRI80 G7 (optic 90x1125mm)
19.840-P Fusion-B 4S 28W 3900lm 4000K CRI80 G7 (optic 90x1125mm)

19.830-P Fusion-B 5S 15W 2100lm 3000K CRI80 G7 (optic 90x1405mm)
19.830-P Fusion-B 5S 18W 2450lm 3000K CRI80 G7 (optic 90x1405mm)
19.830-P Fusion-B 5S 21W 2800lm 3000K CRI80 G7 (optic 90x1405mm)
19.830-P Fusion-B 5S 24W 3150lm 3000K CRI80 G7 (optic 90x1405mm)
19.830-P Fusion-B 5S 28W 3650lm 3000K CRI80 G7 (optic 90x1405mm)
19.840-P Fusion-B 5S 15W 2250lm 4000K CRI80 G7 (optic 90x1405mm)
19.840-P Fusion-B 5S 18W 2650lm 4000K CRI80 G7 (optic 90x1405mm)
19.840-P Fusion-B 5S 21W 3000lm 4000K CRI80 G7 (optic 90x1405mm)
19.840-P Fusion-B 5S 24W 3350lm 4000K CRI80 G7 (optic 90x1405mm)
19.840-P Fusion-B 5S 28W 3900lm 4000K CRI80 G7 (optic 90x1405mm)

19.830-P Fusion-B 3S 16 W 2,100 lm 3,000 K CRI80 G7 (optic 70x845 mm)
19.830-P Fusion-B 3S 19 W 2,400 lm 3,000 K CRI80 G7 (optic 70x845 mm)
19.830-P Fusion-B 3S 22 W 2,750 lm 3,000 K CRI80 G7 (optic 70x845 mm)
19.830-P Fusion-B 3S 24 W 3,050 lm 3,000 K CRI80 G7 (optic 70x845 mm)
19.830-P Fusion-B 3S 29 W 3,550 lm 3,000 K CRI80 G7 (optic 70x845 mm)
19.840-P Fusion-B 3S 16 W 2,250 lm 4,000 K CRI80 G7 (optic 70x845 mm)
19.840-P Fusion-B 3S 19 W 2,600 lm 4,000 K CRI80 G7 (optic 70x845 mm)

19.840-P Fusion-B 3S 22 W 2,950 lm 4,000 K CRI80 G7 (optic 70×845 mm)

19.840-P Fusion-B 3S 24 W 3,300 lm 4,000 K CRI80 G7 (optic 70×845 mm)

19.840-P Fusion-B 3S 29 W 3,850 lm 4,000 K CRI80 G7 (optic 70×845 mm)

19.830-P Fusion-B 4S 16 W 2,100 lm 3,000 K CRI80 G7 (optic 70×1125 mm)

19.830-P Fusion-B 4S 18 W 2,450 lm 3,000 K CRI80 G7 (optic 70×1125 mm)

19.830-P Fusion-B 4S 21 W 2,750 lm 3,000 K CRI80 G7 (optic 70×1125 mm)

19.830-P Fusion-B 4S 24 W 3,100 lm 3,000 K CRI80 G7 (optic 70×1125 mm)

19.830-P Fusion-B 4S 28 W 3,600 lm 3,000 K CRI80 G7 (optic 70×1125 mm)

19.840-P Fusion-B 4S 16 W 2,250 lm 4,000 K CRI80 G7 (optic 70×1125 mm)

19.840-P Fusion-B 4S 18 W 2,650 lm 4,000 K CRI80 G7 (optic 70×1125 mm)

19.840-P Fusion-B 4S 21 W 3,000 lm 4,000 K CRI80 G7 (optic 70×1125 mm)

19.840-P Fusion-B 4S 24 W 3,350 lm 4,000 K CRI80 G7 (optic 70×1125 mm)

19.840-P Fusion-B 4S 24 W 3,350 lm 4,000 K CRI80 G7 (optic 70×1125 mm)

19.830-P Fusion-B 5S 15 W 2,100 lm 3,000 K CRI80 G7 (optic 70×1405 mm)

19.830-P Fusion-B 5S 18 W 2,450 lm 3,000 K CRI80 G7 (optic 70×1405 mm)

19.830-P Fusion-B 5S 21 W 2,800 lm 3,000 K CRI80 G7 (optic 70×1405 mm)

19.830-P Fusion-B 5S 24 W 3,150 lm 3,000 K CRI80 G7 (optic 70×1405 mm)

19.830-P Fusion-B 5S 28 W 3,650 lm 3,000 K CRI80 G7 (optic 70×1405 mm)

19.840-P Fusion-B 5S 15 W 2,250 lm 4,000 K CRI80 G7 (optic 70×1405 mm)

19.840-P Fusion-B 5S 18 W 2,650 lm 4,000 K CRI80 G7 (optic 70×1405 mm)

19.840-P Fusion-B 5S 21 W 3,000 lm 4,000 K CRI80 G7 (optic 70×1405 mm)

19.840-P Fusion-B 5S 24 W 3,350 lm 4,000 K CRI80 G7 (optic 70×1405 mm)

19.840-P Fusion-B 5S 28 W 3,900 lm 4,000 K CRI80 G7 (optic 70×1405 mm)