



FUSION-C

Fusion-C is a surface-mounted luminaire suitable for both general lighting and effective task lighting. The LED luminaire was developed as an alternative to T8 and T5 linear fluorescent luminaires for use in both renovation and new construction projects. The luminaires are made of a slim metal housing finished with a matte white powder coating.

- Surface-mounted luminaire with integrated driver
- Prismatic lens for task lighting with low glare (UGR < 19)
- Versions with integrated light sensor available

Categories: [Climate ceiling fixtures](#)



Fusion-C is a surface-mounted luminaire suitable for both general lighting and effective task lighting. The LED luminaire was developed as an alternative to T8 and T5 linear fluorescent luminaires for use in both renovation and new construction projects. The luminaires are made of a slim metal housing finished with a matte white powder coating.

- Surface-mounted luminaire with integrated driver
- Prismatic lens for task lighting with low glare (UGR < 19)
- Versions with integrated light sensor available

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
Armaturefficiëntie	>140lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Integrated
Energielabel	A++
Family	Fusion
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Acrylic, Aluminium, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Microprismatic lens, Opalen diffusor
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	GST18i5 pastelblauw, Kabel, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz

Shape	Rectangular
Zelfklevende stofkap	Optioneel

PHOTOMETRIC DATA

19.830-P Fusion-C 4S 16W 2100lm 3000K CRI80 G7 (optic 90x1125mm)

19.830-P Fusion-C 4S 18W 2450lm 3000K CRI80 G7 (optic 90x1125mm)

19.830-P Fusion-C 4S 21W 2750lm 3000K CRI80 G7 (optic 90x1125mm)

19.830-P Fusion-C 4S 24W 3100lm 3000K CRI80 G7 (optic 90x1125mm)

19.830-P Fusion-C 4S 28W 3600lm 3000K CRI80 G7 (optic 90x1125mm)

19.840-P Fusion-C 4S 16W 2250lm 4000K CRI80 G7 (optic 90x1125mm)

19.840-P Fusion-C 4S 18W 2650lm 4000K CRI80 G7 (optic 90x1125mm)

19.840-P Fusion-C 4S 21W 3000lm 4000K CRI80 G7 (optic 90x1125mm)

19.840-P Fusion-C 4S 24W 3350lm 4000K CRI80 G7 (optic 90x1125mm)

19.840-P Fusion-C 4S 28W 3900lm 4000K CRI80 G7 (optic 90x1125mm)

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at

<https://atomis.nl/ldt-photometrics/>