



LIGHTSCAPE-C 80

Lightscape-C 80 is a linear pendant luminaire equipped with a micro-prismatic lens (UGR<19) providing uniform and efficient lighting across the entire length of the fixture.

- Architectural design that ensures uniform illumination along the entire length of the fixture
- Office lighting
- Prismatic lens UGR<19

Categories: [Surface-mounted luminaires](#)



PRODUCT IMAGES



Lightscape-C 80 is a linear pendant luminaire equipped with a micro-prismatic lens (UGR<19) providing uniform and efficient lighting across the entire length of the fixture.

- Architectural design that ensures uniform illumination along the entire length of the fixture
- Office lighting
- Prismatic lens UGR<19

NOTES

ADDITIONAL INFORMATION

| | |
|------------------------------------|---|
| Air extraction | N/A |
| Armaturefficiëntie | >140lm/W |
| Bevestiging | ceiling mounting |
| CIE Flux code | 93 100 100 100 100 |
| Driver positie | Integrated |
| Energielabel | A++ |
| Family | Lightscape |
| Photobiological safety | IEC 62471: RG1 (low risc) |
| Glare (UGR) | <19 |
| IP-class | IP20 (upwards)/IP40 (downwards) |
| Isolatieklasse | Class II |
| Kleurconsistentie (SDCM) | SDCM=3 |
| Kleurtemperatuur | Tunable White, 2700K, 3000K, 3500K, 4000K |
| Color Rendering Index (CRI) | CRI90, CRI80 |
| Light control | 1-10V dimming, Casambi dimming, DALI dimming, Optional |
| Luchtafzuiging | n.v.t. |
| Material | Acrylic, Aluminium |
| Emergency lighting | 1 hour emergency power, Optional, Optional 1 hour autonomy self-test |
| Ambient temperature | -20°C / +40°C |
| Optics | Microprismatic lens, Opalen diffusor |
| Oriëntatie | Down |
| Packaging dimensions | Bulk packaging |
| Powerfactor | >9 |
| Primaire aansluitingen | BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver |
| Productkleur | On request |
| Producttoepassing | Education, Hospitality, Office, Public spaces |
| Self-adhesive dust cover | Optional |
| Verpakkingsafmetingen | Bulkverpakking |
| Verwachte levensduur | L90B50@60,000h (Tq 25°C) |

| | |
|-----------------------------|---------------------|
| Voltage / frequentie | 220-240V, 50 / 60Hz |
| Shape | Rectangular |
| Zelfklevende stofkap | Optioneel |

