




INLITE 170

Inlite is a range of high-quality recessed LED downlights equipped with a glare-reducing reflector and a satin diffuser.

- High-efficiency LED for enhanced lumen performance
- White trim
- UGR < 19

Categories: [Downlights and recessed spotlights](#)



PRODUCT IMAGES



Inlite is a range of high-quality recessed LED downlights equipped with a glare-reducing reflector and a satin diffuser.

- High-efficiency LED for enhanced lumen performance
- White trim
- UGR < 19

NOTES

ADDITIONAL INFORMATION

| | |
|------------------------------------|---|
| Air extraction | N/A |
| Armaturefficiëntie | >125lm/W |
| Bevestiging | ceiling mounting |
| CIE Flux code | 93 100 100 100 100 |
| Driver positie | Loose driver |
| Energielabel | A++ |
| Family | Meson |
| Photobiological safety | IEC 62471: RG1 (low risc) |
| Glare (UGR) | <19 |
| IP-class | IP20 (upwards)/IP40 (downwards) |
| Isolatieklasse | Class II |
| Kleurconsistentie (SDCM) | SDCM=2 |
| Kleurtemperatuur | Tunable White, 2700K, 3000K, 3500K, 4000K |
| Color Rendering Index (CRI) | CRI97, CRI90, CRI80 |
| Light control | 1-10V dimming, Casambi dimming, DALI dimming, Optional |
| Luchtafzuiging | n.v.t. |
| Material | Acrylic, Steel |
| Emergency lighting | 1 hour emergency power, Optional, Optional 1 hour autonomy self-test |
| Ambient temperature | -20°C / +40°C |
| Optics | Opalen diffusor, Reflector |
| Oriëntatie | Down |
| Packaging dimensions | Bulk packaging |
| Powerfactor | >9 |
| Primaire aansluitingen | BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver |
| Productkleur | On request |
| Producttoepassing | Education, Hospitality, Office, Public spaces |
| Self-adhesive dust cover | Optional |
| Verpakkingsafmetingen | Bulkverpakking |
| Verwachte levensduur | L90B50@60,000h (Tq 25°C) |

| | |
|-----------------------------|---------------------|
| Voltage / frequentie | 220-240V, 50 / 60Hz |
| Shape | Round |
| Cut-out size | 150mm |
| Zelfklevende stofkap | Optioneel |

PHOTOMETRIC DATA

46205.30 Meson pro 190 9W 1100lm 3000K CRI80 UGR16 G7
46207.30 Meson pro 190 15W 1750lm 3000K CRI80 UGR18 G7
46216.30 Meson pro 190 20W 2150lm 3000K CRI80 UGR19 G7
46218.30 Meson pro 190 26W 2700lm 3000K CRI80 UGR19 G7

46205.40 Meson pro 190 9W 1150lm 4000K CRI80 UGR16 G7
46207.40 Meson pro 190 15W 1800lm 4000K CRI80 UGR18 G7
46216.40 Meson pro 190 20W 2200lm 4000K CRI80 UGR19 G7
46218.40 Meson pro 190 26W 2750lm 4000K CRI80 UGR19 G7

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at
<https://atomis.nl/ldt-photometrics/>