



MESON REFIT PRO

Meson Refit pro is an efficient recessed LED downlight suitable for a wide range of existing ceiling cut-outs.

- Decorative cover ring
- Suitable for a wide variety of existing ceiling cut-outs (Ø185 - 230mm)
- Luminaires efficiency > 125lm/W




Downloads

[Photometrics Meson Refit pro](#)



Categories: [Downlights and recessed spotlights](#)






PRODUCT IMAGES



Glare Evaluation According to UGR										
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
	70	70	50	50	30	70	70	50	50	30
	p Ceiling	p Walls	p Ceilings	p Walls	p Ceilings	p Ceiling	p Walls	p Ceilings	p Walls	p Ceilings
ZH	24	19.0	19.2	19.2	20.1	19.0	19.7	19.0	19.9	20.1
	34	18.8	19.5	19.1	19.7	18.9	18.9	18.1	19.7	19.9
	44	18.8	19.4	19.1	19.6	19.9	18.5	19.4	19.1	19.6
	64	18.7	19.2	19.0	19.5	19.8	18.7	19.2	19.0	19.5
	84	18.6	19.2	19.0	19.5	19.8	18.6	19.2	19.0	19.5
	12H	18.6	19.1	19.0	19.4	19.7	18.6	19.1	19.0	19.7
4H	24	18.8	19.4	19.2	19.6	19.9	18.8	19.4	19.1	19.6
	34	18.6	19.1	19.0	19.4	19.6	18.6	19.1	19.0	19.4
	44	18.6	19.0	18.9	19.3	19.7	18.6	19.0	18.9	19.3
	64	18.5	18.9	18.9	19.2	19.6	18.5	18.9	18.9	19.2
	84	18.5	18.8	18.9	19.2	19.6	18.5	18.8	18.5	19.2
	12H	18.4	18.7	18.8	19.1	19.5	18.4	18.7	18.8	19.1
8H	44	18.5	18.6	18.5	19.2	19.8	18.5	18.8	18.5	19.2
	64	18.5	18.6	18.5	19.2	19.8	18.5	18.8	18.5	19.2
	84	18.3	18.5	18.6	19.0	19.4	18.3	18.6	18.0	19.4
	12H	18.3	18.4	18.5	18.9	19.4	18.3	18.4	18.3	18.9
12H	44	18.4	18.7	18.8	19.1	19.5	18.4	18.7	18.8	19.1
	64	18.3	18.5	18.6	19.0	19.4	18.3	18.5	18.5	19.0
	84	18.3	18.4	18.5	18.9	19.4	18.3	18.4	18.3	18.9





Meson Refit pro is an efficient recessed LED downlight suitable for a wide range of existing ceiling cut-outs.

- Decorative cover ring
- Suitable for a wide variety of existing ceiling cut-outs (Ø185 - 230mm)
- Luminaire efficiency > 125lm/W

Downloads

[Photometrics Meson Refit pro](#)

NOTES

ADDITIONAL INFORMATION

Isolatieklasse	Class II
Driver positie	Loose driver
Light control	1-10V dimming, Casambi dimming, DALI dimming
Producttoepassing	Education, Hospitality, Office, Public spaces
Oriëntatie	Down
Kleurtemperatuur	Tunable White, 2700K
Ambient temperature	-20°C / +40°C
Shape	Round
Material	Acrylic, Steel
Bevestiging	Recessed
Photobiological safety	IEC 62471: RG1 (low risc)
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Family	Meson

