



## MESON ROUND 190 REFIT

Meson Round 190 Refit is a series of powerful LED recessed spotlights with power LEDs covered by a prismatic lens or a double frosted diffuser. Meson Round 190 Refit is identical to Meson Round 190, but with a wider cover. The shielding is countersunk behind a matte or high-gloss reflector.

- Easy installation with spring clips
- Suitable for existing cutouts from Ø185 to Ø230mm
- Trim ring in white, black, or silver
- Reflector ring available in matte anodized, glossy anodized, matte black, or matte white
- Opal diffuser or prismatic lens

### Downloads

[Photometrics Meson Round 190](#)

**Categories:** [Downlights and recessed spotlights](#), [Refurbishment and Retrofit Fixtures](#)



## PRODUCT IMAGES



Meson Round 190 Refit is a series of powerful LED recessed spotlights with power LEDs covered by a prismatic lens or a double frosted diffuser. Meson Round 190 Refit is identical to Meson Round 190, but with a wider cover. The shielding is countersunk behind a matte or high-gloss reflector.

- Easy installation with spring clips
- Suitable for existing cutouts from Ø185 to Ø230mm
- Trim ring in white, black, or silver
- Reflector ring available in matte anodized, glossy anodized, matte black, or matte white
- Opal diffuser or prismatic lens

### Downloads

[Photometrics Meson Round 190](#)

## NOTES

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Air extraction</b>	N/A
<b>Armaturefficiëntie</b>	>125lm/W
<b>Bevestiging</b>	Recessed
<b>CIE Flux code</b>	93 100 100 100 100
<b>Driver positie</b>	Loose driver
<b>Energielabel</b>	A++
<b>Family</b>	Meson
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Glare (UGR)</b>	<19
<b>IP-class</b>	IP20 (upwards)/IP40 (downwards)
<b>Isolatieklasse</b>	Class II
<b>Kleurconsistentie (SDCM)</b>	SDCM=2
<b>Kleurtemperatuur</b>	Tunable White, 2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI97, CRI90, CRI80
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Luchtafzuiging</b>	n.v.t.
<b>Material</b>	Acrylic, Steel
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Opalen diffusor
<b>Oriëntatie</b>	Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
<b>Productkleur</b>	On request
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces
<b>Self-adhesive dust cover</b>	Optional
<b>Verpakkingsafmetingen</b>	Bulkverpakking
<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)

<b>Voltage / frequentie</b>	220-240V, 50 / 60Hz
<b>Shape</b>	Round
<b>Zelfklevende stofkap</b>	Optioneel

