



MESON ROUND 190 REFIT

Meson Round 190 Refit is a series of powerful LED recessed spotlights with power LEDs covered by a prismatic lens or a double frosted diffuser. Meson Round 190 Refit is identical to Meson Round 190, but with a wider cover. The shielding is countersunk behind a matte or high-gloss reflector.

- Easy installation with spring clips
- Suitable for existing cutouts from Ø185 to Ø230mm
- Trim ring in white, black, or silver
- Reflector ring available in matte anodized, glossy anodized, matte black, or matte white
- Opal diffuser or prismatic lens

Categories: [Downlights and recessed spotlights](#), [Refurbishment and Retrofit Fixtures](#)



PRODUCT IMAGES



Meson Round 190 Refit is a series of powerful LED recessed spotlights with power LEDs covered by a prismatic lens or a double frosted diffuser. Meson Round 190 Refit is identical to Meson Round 190, but with a wider cover. The shielding is countersunk behind a matte or high-gloss reflector.

- Easy installation with spring clips
- Suitable for existing cutouts from Ø185 to Ø230mm
- Trim ring in white, black, or silver
- Reflector ring available in matte anodized, glossy anodized, matte black, or matte white
- Opal diffuser or prismatic lens

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
Armaturefficiëntie	>125lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Loose driver
Energielabel	A++
Family	Meson
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=2
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI97, CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Acrylic, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Opalen diffusor
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)

Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Round
Zelfklevende stofkap	Optioneel

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at
<https://atomis.nl/ldt-photometrics/>