



MESON ROUND 190 WALLWASHER REFIT

Meson round 190 wallwasher Refit is a high-quality LED recessed downlight with asymmetric light distribution. To ensure uniform lighting across the entire surface, the distance to the wall for wallwashers must not exceed 50-60 cm. The central unit can be rotated within the trim ring to adjust the spot direction. Refit versions are identical to the standard Meson versions. However, the trim ring is larger, not Ø190mm but Ø245mm.

- Provides uniform wall lighting
- The central unit can be rotated within the trim ring to adjust the spot direction
- Particularly suitable for retail lighting
- Low-glare lighting
- Wider trim ring: Ø245 mm

Categories: [Downlights and recessed spotlights](#)



PRODUCT IMAGES

Meson round 190 wallwasher Refit is a high-quality LED recessed downlight with asymmetric light distribution. To ensure uniform lighting across the entire surface, the distance to the wall for wallwashers must not exceed 50-60 cm. The central unit can be rotated within the trim ring to adjust the spot direction. Refit versions are identical to the standard Meson versions. However, the trim ring is larger, not Ø190mm but Ø245mm.

- Provides uniform wall lighting
- The central unit can be rotated within the trim ring to adjust the spot direction
- Particularly suitable for retail lighting
- Low-glare lighting
- Wider trim ring: Ø245 mm

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
Armaturefficiëntie	>125lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Loose driver
Energielabel	A++
Family	Meson
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19, UGR<22
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=2
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI97, CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Acrylic, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Reflector
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Exhibition spaces, Hospitality, Office, Public spaces, Retail
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)

Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Round
Zelfklevende stofkap	Optioneel

PHOTOMETRIC DATA

44562.30 Meson round 190 wallwasher 15W 1750lm 3000K CRI80 G7

44562.40 Meson round 190 wallwasher 15W 1800lm 4000K CRI80 G7

44565.30 Meson round 190 wallwasher 21W 2350lm 3000K CRI80 G7

44565.40 Meson round 190 wallwasher 21W 2450lm 4000K CRI80 G7

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at

<https://atomis.nl/ldt-photometrics/>