



MESON ROUND 190 WALLWASHER

Meson round 190 wallwasher is a high-quality LED recessed downlight with asymmetric light distribution. To ensure uniform lighting across the entire surface, the distance to the wall for wallwashers must not exceed 50-60 cm. The central unit can be rotated within the trim ring to adjust the beam direction.

- Provides uniform wall lighting
- The central unit can be rotated within the trim ring to adjust the spot direction
- Particularly suitable for retail lighting
- Low-glare lighting

Categories: [Downlights and recessed spotlights](#)



PRODUCT IMAGES

Meson round 190 wallwasher is a high-quality LED recessed downlight with asymmetric light distribution. To ensure uniform lighting across the entire surface, the distance to the wall for wallwashers must not exceed 50-60 cm. The central unit can be rotated within the trim ring to adjust the beam direction.

- Provides uniform wall lighting
- The central unit can be rotated within the trim ring to adjust the spot direction
- Particularly suitable for retail lighting
- Low-glare lighting

NOTES

ADDITIONAL INFORMATION

| | |
|------------------------------------|---|
| Air extraction | N/A |
| Armaturefficiëntie | >125lm/W |
| Bevestiging | Recessed |
| CIE Flux code | 93 100 100 100 100 |
| Driver positie | Loose driver |
| Energielabel | A++ |
| Family | Meson |
| Photobiological safety | IEC 62471: RG1 (low risc) |
| Glare (UGR) | <19, UGR<22 |
| IP-class | IP20 (upwards)/IP40 (downwards) |
| Isolatieklasse | Class II |
| Kleurconsistentie (SDCM) | SDCM=2 |
| Kleurtemperatuur | Tunable White, 2700K, 3000K, 3500K, 4000K |
| Color Rendering Index (CRI) | CRI97, CRI90, CRI80 |
| Light control | 1-10V dimming, Casambi dimming, DALI dimming, Optional |
| Luchtafzuiging | n.v.t. |
| Material | Acrylic, Steel |
| Emergency lighting | 1 hour emergency power, Optional, Optional 1 hour autonomy self-test |
| Ambient temperature | -20°C / +40°C |
| Optics | Reflector |
| Oriëntatie | Down |
| Packaging dimensions | Bulk packaging |
| Powerfactor | >9 |
| Primaire aansluitingen | BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver |
| Productkleur | On request |
| Producttoepassing | Education, Exhibition spaces, Hospitality, Office, Public spaces, Retail |
| Self-adhesive dust cover | Optional |
| Verpakkingsafmetingen | Bulkverpakking |
| Verwachte levensduur | L90B50@60,000h (Tq 25°C) |

| | |
|-----------------------------|---------------------|
| Voltage / frequentie | 220-240V, 50 / 60Hz |
| Shape | Round |
| Cut-out size | ∅170mm |
| Zelfklevende stofkap | Optioneel |

PHOTOMETRIC DATA

44562.30 Meson round 190 wallwasher 15W 1750lm 3000K CRI80 G7

44562.40 Meson round 190 wallwasher 15W 1800lm 4000K CRI80 G7

44565.30 Meson round 190 wallwasher 21W 2350lm 3000K CRI80 G7

44565.40 Meson round 190 wallwasher 21W 2450lm 4000K CRI80 G7

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at

<https://atomis.nl/ldt-photometrics/>