



MESON ROUND 220 AQUA

Meson round 220 Aqua is an IP65 high-quality recessed downlight specifically designed for use above swimming pools and other wet areas. The cover and opal diffuser are made of plastic. The fixture is equipped with a set of three polyamide screws for mounting in suspended ceilings.

- IP65 housing (on the underside)
- Installation with a set of three polyamide screws
- Corrosion-free safety lighting
- White edge and opal polycarbonate diffuser




Downloads

[Photometrics Meson aqua](#)

Categories: [Downlights and recessed spotlights](#)



PRODUCT IMAGES




f-waardering volgens UGR									
		Perspectief divers t.o.v. lampenpas					Perspectief langs t.o.v. lampenpas		
Ruimteafmeting		X	Y	2H	3H	4H	8H	12H	24H
p Plafond	70	70	50	50	30	70	70	50	50
p Muuren	50	30	50	30	30	50	30	50	30
p Vloer	20	20	20	20	20	20	20	20	20

Variatie op waarmespatiede voor lampstanden S

S = 1.0H	+1.7 / -2.5	+1.8 / -2.5
S = 1.5H	+3.7 / -3.2	+3.7 / -3.3
S = 2.0H	+5.5 / -3.0	+5.5 / -3.2

Standartaartabel

BK01	BK01
Correctie-opticaal	-0.3
Gecorrigeerde verbindingsindicatie in relatie tot 2492lm Totale lichtstroom	-0.3



Meson round 220 Aqua is an IP65 high-quality recessed downlight specifically designed for use above swimming pools and other wet areas. The cover and opal diffuser are made of plastic. The fixture is equipped with a set of three polyamide screws for mounting in suspended ceilings.

- IP65 housing (on the underside)
- Installation with a set of three polyamide screws
- Corrosion-free safety lighting
- White edge and opal polycarbonate diffuser

Downloads

[Photometrics Meson aqua](#)

NOTES

ADDITIONAL INFORMATION

Isolatieklasse	Class II
Driver positie	Loose driver
Light control	1-10V dimming, Casambi dimming, DALI dimming
Producttoepassing	Education, Hospitality, Office, Public spaces
Optics	Opalen diffusor
Oriëntatie	Down
Kleurtemperatuur	Tunable White, 2700K
Ambient temperature	-20°C / +40°C
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Shape	Round
Material	Acrylic, Steel
Productkleur	On request
Bevestiging	Recessed
Photobiological safety	IEC 62471: RG1 (low risc)
Color Rendering Index (CRI)	CRI97, CRI90, CRI80
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Family	Meson
Kleurconsistentie (SDCM)	SDCM=2
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Powerfactor	>0.9
Energielabel	A++

