



METRONOME-C

Metronome-C is a linear LED luminaire equipped with 20, 28, or 36 lenses, recessed behind a grid louver. This LED luminaire is a completely new lighting solution for effective illumination with an architectural appearance. A choice can be made between UGR< 19 optics (standard) and UGR< 16.

- Architectural aesthetic with 20, 28, or 36 optics
- Choice between UGR< 19 and UGR< 16 optics
- Louver finish white or high-gloss aluminum
- Flat design for shallow ceiling depths

Categories: [Surface-mounted luminaires](#)



Metronome-C is a linear LED luminaire equipped with 20, 28, or 36 lenses, recessed behind a grid louver. This LED luminaire is a completely new lighting solution for effective illumination with an architectural appearance. A choice can be made between UGR < 19 optics (standard) and UGR < 16.

- Architectural aesthetic with 20, 28, or 36 optics
- Choice between UGR < 19 and UGR < 16 optics
- Louver finish white or high-gloss aluminum
- Flat design for shallow ceiling depths

NOTES

ADDITIONAL INFORMATION

Air extraction	Optional
Armaturefficiëntie	>140lm/W
Bevestiging	ceiling mounting
CIE Flux code	93 100 100 100 100
Driver positie	Attached to the fixture, Loose driver
Energielabel	A++
Family	Metronome
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class-I
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	Optioneel
Material	Acrylic, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens en louver
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	On request, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Specificaties	G8A1 / 06-02-2025
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)

Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Rectangular
Zelfklevende stofkap	Optioneel

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at

<https://atomis.nl/ldt-photometrics/>