



## METRONOME-C

Metronome-C is a linear LED fixture equipped with 20, 28, or 36 lenses recessed behind a grid louver. This fixture is a completely new lighting solution for effective illumination with an architectural aesthetic. Choose between UGR< 19 optics (standard) and UGR< 16.

- Architectural aesthetic with 20, 28, or 36 optics
- Choice of UGR< 19 or UGR< 16 optics.
- Louver finish white or high-gloss aluminum
- Flat design for shallow ceiling depths

### Downloads

[Metronome-C Photometrics](#)

Categories: [Surface-mounted luminaires](#)



Metronome-C is a linear LED fixture equipped with 20, 28, or 36 lenses recessed behind a grid louver. This fixture is a completely new lighting solution for effective illumination with an architectural aesthetic. Choose between UGR< 19 optics (standard) and UGR< 16.

- Architectural aesthetic with 20, 28, or 36 optics
- Choice of UGR< 19 or UGR< 16 optics.
- Louver finish white or high-gloss aluminum
- Flat design for shallow ceiling depths

## Downloads

[Metronome-C Photometrics](#)

## NOTES

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Air extraction</b>	Optional
<b>Armaturefficiëntie</b>	>140lm/W
<b>Bevestiging</b>	ceiling mounting
<b>CIE Flux code</b>	93 100 100 100 100
<b>Driver positie</b>	Attached to the fixture, Loose driver
<b>Energielabel</b>	A++
<b>Family</b>	Metronome
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Glare (UGR)</b>	<19
<b>IP-class</b>	IP20 (upwards)/IP40 (downwards)
<b>Isolatieklasse</b>	Class-I
<b>Kleurconsistentie (SDCM)</b>	SDCM=3
<b>Kleurtemperatuur</b>	Tunable White, 2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI90, CRI80
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Luchtafzuiging</b>	Optioneel
<b>Material</b>	Acrylic, Steel
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Lens en louver
<b>Oriëntatie</b>	Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	On request, On the driver
<b>Productkleur</b>	On request
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces
<b>Self-adhesive dust cover</b>	Optional
<b>Specificaties</b>	G8A1 / 06-02-2025
<b>Verpakkingsafmetingen</b>	Bulkverpakking
<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)

<b>Voltage / frequentie</b>	220-240V, 50 / 60Hz
<b>Shape</b>	Rectangular
<b>Zelfklevende stofkap</b>	Optioneel

