



METRONOME-K

Metronome-K is a linear LED luminaire featuring 20, 28, or 36 lenses, recessed behind a grid louver. This LED luminaire is a completely new lighting solution for effective illumination with an architectural aesthetic. Choose between UGR< 19 optics (standard) and UGR< 16.

- Architectural aesthetic with 20, 28, or 36 optics
- Choice of UGR< 19 or UGR< 16 optics.
- Louver finish white or high-gloss aluminum
- Flat design for shallow ceiling depths

Downloads

[Photometrics Metronome-K](#)

Categories: [Climate ceiling fixtures](#)



Metronome-K is a linear LED luminaire featuring 20, 28, or 36 lenses, recessed behind a grid louver. This LED luminaire is a completely new lighting solution for effective illumination with an architectural aesthetic. Choose between UGR< 19 optics (standard) and UGR< 16.

- Architectural aesthetic with 20, 28, or 36 optics
- Choice of UGR< 19 or UGR< 16 optics.
- Louver finish white or high-gloss aluminum
- Flat design for shallow ceiling depths

Downloads

[Photometrics Metronome-K](#)

NOTES

ADDITIONAL INFORMATION

Air extraction	Optional
Armaturefficiëntie	>140lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Attached to the fixture, Loose driver
Energielabel	A++
Family	Metronome
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	Optioneel
Material	Acrylic, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens en louver
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Specificaties	G8A1 / 06-02-2025
Verpakkingsafmetingen	Bulkverpakking

Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Rectangular
Zelfklevende stofkap	Optioneel

PHOTOMETRIC DATA

12.830K.100×900.20 Metronome-K 6W 1000lm 3000K CRI80 G7 UGR19
12.830K.100×900.20 Metronome-K 6W 1100lm 3000K CRI80 G7 UGR19
12.830K.100×900.20 Metronome-K 7W 1200lm 3000K CRI80 G7 UGR19
12.830K.100×900.20 Metronome-K 9W 1500lm 3000K CRI80 G7 UGR19
12.830K.100×900.20 Metronome-K 10W 1700lm 3000K CRI80 G7 UGR19
12.830K.100×900.20 Metronome-K 13W 2100lm 3000K CRI80 G7 UGR19
12.830K.100×900.20 Metronome-K 16W 2500lm 3000K CRI80 G7 UGR19
12.830K.100×900.20 Metronome-K 18W 2800lm 3000K CRI80 G7 UGR19

12.830K.100×1200.28 Metronome-K 9W 1600lm 3000K CRI80 G7 UGR19
12.830K.100×1200.28 Metronome-K 10W 1700lm 3000K CRI80 G7 UGR19
12.830K.100×1200.28 Metronome-K 12W 1900lm 3000K CRI80 G7 UGR19
12.830K.100×1200.28 Metronome-K 14W 2300lm 3000K CRI80 G7 UGR19
12.830K.100×1200.28 Metronome-K 17W 2700lm 3000K CRI80 G7 UGR19
12.830K.100×1200.28 Metronome-K 21W 3400lm 3000K CRI80 G7 UGR19
12.830K.100×1200.28 Metronome-K 25W 4000lm 3000K CRI80 G7 UGR19
12.830K.100×1200.28 Metronome-K 29W 4500lm 3000K CRI80 G7 UGR19

12.830K.600×600.32 Metronome-K 9W 1600lm 3000K CRI80 G7 UGR19
12.830K.600×600.32 Metronome-K 11W 1800lm 3000K CRI80 G7 UGR19
12.830K.600×600.32 Metronome-K 12W 2000lm 3000K CRI80 G7 UGR19
12.830K.600×600.32 Metronome-K 15W 2300lm 3000K CRI80 G7 UGR19
12.830K.600×600.32 Metronome-K 17W 2600lm 3000K CRI80 G7 UGR19
12.830K.600×600.32 Metronome-K 19W 2900lm 3000K CRI80 G7 UGR19
12.830K.600×600.32 Metronome-K 22W 3200lm 3000K CRI80 G7 UGR19
12.830K.600×600.32 Metronome-K 24W 3400lm 3000K CRI80 G7 UGR19

12.830K.100×1500.36 Metronome-K 12W 1900lm 3000K CRI80 G7 UGR19
12.830K.100×1500.36 Metronome-K 13W 2100lm 3000K CRI80 G7 UGR19
12.830K.100×1500.36 Metronome-K 16W 2600lm 3000K CRI80 G7 UGR19
12.830K.100×1500.36 Metronome-K 19W 3000lm 3000K CRI80 G7 UGR19
12.830K.100×1500.36 Metronome-K 21W 3400lm 3000K CRI80 G7 UGR19
12.830K.100×1500.36 Metronome-K 24W 3800lm 3000K CRI80 G7 UGR19
12.830K.100×1500.36 Metronome-K 28W 4500lm 3000K CRI80 G7 UGR19
12.830K.100×1500.36 Metronome-K 32W 5100lm 3000K CRI80 G7 UGR19

12.840K.100×900.20 Metronome-K 6W 1000lm 4000K CRI80 G7 UGR19
12.840K.100×900.20 Metronome-K 6W 1100lm 4000K CRI80 G7 UGR19
12.840K.100×900.20 Metronome-K 7W 1200lm 4000K CRI80 G7 UGR19
12.840K.100×900.20 Metronome-K 9W 1500lm 4000K CRI80 G7 UGR19
12.840K.100×900.20 Metronome-K 10W 2800lm 4000K CRI80 G7 UGR19

12.840K.100×900.20 Metronome-K 13W 2200lm 4000K CRI80 G7 UGR19
12.840K.100×900.20 Metronome-K 16W 2600lm 4000K CRI80 G7 UGR19
12.840K.100×900.20 Metronome-K 18W 3000lm 4000K CRI80 G7 UGR19

12.840K.100×1200.28 Metronome-K 9W 1600lm 4000K CRI80 G7 UGR19
12.840K.100×1200.28 Metronome-K 10W 1800lm 4000K CRI80 G7 UGR19
12.840K.100×1200.28 Metronome-K 12W 2000lm 4000K CRI80 G7 UGR19
12.840K.100×1200.28 Metronome-K 14W 2400lm 4000K CRI80 G7 UGR19
12.840K.100×1200.28 Metronome-K 17W 2800lm 4000K CRI80 G7 UGR19
12.840K.100×1200.28 Metronome-K 21W 3600lm 4000K CRI80 G7 UGR19
12.840K.100×1200.28 Metronome-K 25W 4100lm 4000K CRI80 G7 UGR19
12.840K.100×1200.28 Metronome-K 29W 4700lm 4000K CRI80 G7 UGR19

12.840K.600×600.32 Metronome-K 9W 1800lm 4000K CRI80 G7 UGR19
12.840K.600×600.32 Metronome-K 11W 2000lm 4000K CRI80 G7 UGR19
12.840K.600×600.32 Metronome-K 12W 2100lm 4000K CRI80 G7 UGR19
12.840K.600×600.32 Metronome-K 15W 2600lm 4000K CRI80 G7 UGR19
12.840K.600×600.32 Metronome-K 17W 3000lm 4000K CRI80 G7 UGR19
12.840K.600×600.32 Metronome-K 19W 3400lm 4000K CRI80 G7 UGR19
12.840K.600×600.32 Metronome-K 22W 3800lm 4000K CRI80 G7 UGR19
12.840K.600×600.32 Metronome-K 24W 4200lm 4000K CRI80 G7 UGR19

12.840K.100×1500.36 Metronome-K 12W 2000lm 4000K CRI80 G7 UGR19
12.840K.100×1500.36 Metronome-K 13W 2200lm 4000K CRI80 G7 UGR19
12.840K.100×1500.36 Metronome-K 16W 2700lm 4000K CRI80 G7 UGR19
12.840K.100×1500.36 Metronome-K 19W 3200lm 4000K CRI80 G7 UGR19
12.840K.100×1500.36 Metronome-K 21W 3600lm 4000K CRI80 G7 UGR19
12.840K.100×1500.36 Metronome-K 24W 4000lm 4000K CRI80 G7 UGR19
12.840K.100×1500.36 Metronome-K 28W 4700lm 4000K CRI80 G7 UGR19
12.840K.100×1500.36 Metronome-K 32W 5300lm 4000K CRI80 G7 UGR19

12.830K.100×1700.36 Metronome-K 12W 2000lm 3000K CRI80 G8 UGR19 RKBIN
12.830K.100×1700.36 Metronome-K 13W 2200lm 3000K CRI80 G8 UGR19 RKBIN
12.830K.100×1700.36 Metronome-K 16W 2700lm 3000K CRI80 G8 UGR19 RKBIN
12.830K.100×1700.36 Metronome-K 19W 3200lm 3000K CRI80 G8 UGR19 RKBIN
12.830K.100×1700.36 Metronome-K 22W 3600lm 3000K CRI80 G8 UGR19 RKBIN
12.830K.100×1700.36 Metronome-K 25W 4000lm 3000K CRI80 G8 UGR19 RKBIN
12.830K.100×1700.36 Metronome-K 29W 4600lm 3000K CRI80 G8 UGR19 RKBIN
12.830K.100×1700.36 Metronome-K 33W 5400lm 3000K CRI80 G8 UGR19 RKBIN

12.840K.100×900.20 Metronome-K 6W 1000lm 4000K CRI80 G7 UGR19
12.840K.100×900.20 Metronome-K 6W 1100lm 4000K CRI80 G7 UGR19
12.840K.100×900.20 Metronome-K 7W 1200lm 4000K CRI80 G7 UGR19
12.840K.100×900.20 Metronome-K 9W 1500lm 4000K CRI80 G7 UGR19

12.840K.100×900.20 Metronome-K 10W 2800lm 4000K CRI80 G7 UGR19

12.840K.100×900.20 Metronome-K 13W 2200lm 4000K CRI80 G7 UGR19

12.840K.100×900.20 Metronome-K 16W 2600lm 4000K CRI80 G7 UGR19

12.840K.100×900.20 Metronome-K 18W 3000lm 4000K CRI80 G7 UGR19

12.840K.100×1700.36 Metronome-K 12W 2100lm 4000K CRI80 G8 UGR19 RKBIN

12.840K.100×1700.36 Metronome-K 13W 2300lm 4000K CRI80 G8 UGR19 RKBIN

12.840K.100×1700.36 Metronome-K 16W 2800lm 4000K CRI80 G8 UGR19 RKBIN

12.840K.100×1700.36 Metronome-K 19W 3300lm 4000K CRI80 G8 UGR19 RKBIN

12.840K.100×1700.36 Metronome-K 22W 3800lm 4000K CRI80 G8 UGR19 RKBIN

12.840K.100×1700.36 Metronome-K 25W 4200lm 4000K CRI80 G8 UGR19 RKBIN

12.840K.100×1700.36 Metronome-K 29W 4900lm 4000K CRI80 G8 UGR19 RKBIN

12.840K.100×1700.36 Metronome-K 33W 5600lm 4000K CRI80 G8 UGR19 RKBIN