



MIRO-M 600X600 MODEL 2

Miro-M 600×600 Model 2 is a square LED fixture featuring 32 recessed lenses positioned behind a grid-shaped louver. This innovative lighting fixture provides effective illumination while adding elegance to any architectural environment. Customers can choose from two different optics: the standard UGR19 or the UGR16. The fixtures are made of powder-coated steel and are custom-made for any ceiling system.

- Architectural design with 32 optics
- Choice of UGR< 19 or UGR< 16 optics.
- Louver in matte black and matte white
- Flat design for shallow ceiling depths

Categories: [Recessed and lay-in luminaires](#)



Miro-M 600×600 Model 2 is a square LED fixture featuring 32 recessed lenses positioned behind a grid-shaped louver. This innovative lighting fixture provides effective illumination while adding elegance to any architectural environment. Customers can choose from two different optics: the standard UGR19 or the UGR16. The fixtures are made of powder-coated steel and are custom-made for any ceiling system.

- Architectural design with 32 optics
- Choice of UGR< 19 or UGR< 16 optics.
- Louver in matte black and matte white
- Flat design for shallow ceiling depths

NOTES

ADDITIONAL INFORMATION

Armaturefficiëntie	>140lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Attached to the fixture, Loose driver
Energielabel	A++
Family	Miro
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI97, CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	Optioneel
Material	Acrylic, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens en louver
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Shape	Square
Zelfklevende stofkap	Optioneel

