



MYOS-M MULTIOPTIC® LINEAR

Myos-M Multioptic Linear is a series of innovative recessed luminaires with mid-power LED modules, utilizing Multioptic® lens technology, specifically designed for use with visible grid suspended ceilings. The optical system features a lens array of 99 mid-power LEDs behind a decorative diaphragm mask.

- Integrates seamlessly into visible grid ceilings
- Architectural design
- Equipped with 99 lenses (UGR < 16-19)

Categories: [Recessed and lay-in luminaires](#)



PRODUCT IMAGES

f-waardering volgens UGR											
p. Plafond		70	70	50	50	30	70	70	50	50	30
p. Muren		50	30	50	30	30	50	30	50	30	30
p. Vloer		20	20	20	20	20	20	20	20	20	20
Ruimteafmeting		Perspectief dwars					Perspectief langs				
X	Y	t.o.v. lampen					t.o.v. lampen				
2H	2H	18.4	19.3	18.6	19.5	19.7	18.3	19.2	18.6	19.5	19.7
	3H	18.5	19.3	18.9	19.6	19.8	18.5	19.3	18.9	19.5	19.8
	4H	18.5	19.3	18.9	19.6	19.9	18.5	19.3	18.8	19.6	19.8
	6H	18.6	19.3	19.0	19.6	19.9	18.6	19.3	18.9	19.6	19.9
	8H	18.7	19.3	19.0	19.7	20.0	18.6	19.3	19.0	19.6	19.9
4H	2H	18.3	19.1	18.7	19.4	19.7	18.3	19.1	18.6	19.4	19.6
	3H	18.5	19.2	18.9	19.5	19.8	18.5	19.2	18.9	19.5	19.8
	4H	18.7	19.2	19.1	19.6	19.9	18.7	19.2	19.0	19.6	19.9
	6H	18.8	19.3	19.2	19.7	20.1	18.8	19.3	19.2	19.7	20.1
	8H	18.9	19.3	19.3	19.7	20.2	18.9	19.3	19.3	19.7	20.2
8H	2H	19.0	19.4	19.4	19.8	20.2	19.0	19.4	19.4	19.8	20.2
	4H	18.7	19.1	19.1	19.5	19.9	18.6	19.1	19.1	19.5	19.9
	6H	18.9	19.2	19.3	19.7	20.1	18.9	19.2	19.4	19.7	20.1
	8H	19.0	19.3	19.5	19.8	20.3	19.0	19.3	19.5	19.8	20.3
	12H	19.1	19.4	19.6	19.8	20.4	19.2	19.4	19.7	19.9	20.4
12H	4H	18.6	19.0	19.1	19.4	19.9	18.6	19.0	19.1	19.4	19.9
	6H	18.9	19.2	19.4	19.6	20.1	18.9	19.2	19.4	19.6	20.1
	8H	19.0	19.3	19.5	19.8	20.3	19.0	19.3	19.5	19.8	20.3

Varieatie op samenstelling voor lampafstanden S

S = 1.0H	+1.0 / -1.7	+1.0 / -1.7
S = 1.5H	+2.4 / -2.9	+2.4 / -2.9
S = 2.0H	+4.1 / -3.6	+4.0 / -3.6

Standaardtabel	BK01	BK01
Correctie-optalstal	0.9	0.9

Gecorrigeerde verblindingindicatie in relatie tot 2625lm Totale lichtstroom

Myos-M Multioptic Linear is a series of innovative recessed luminaires with mid-power LED modules, utilizing Multioptic® lens technology, specifically designed for use with visible grid suspended ceilings. The optical system features a lens array of 99 mid-power LEDs behind a decorative diaphragm mask.

- Integrates seamlessly into visible grid ceilings
- Architectural design
- Equipped with 99 lenses (UGR< 16-19)

NOTES

ADDITIONAL INFORMATION

Air extraction	Optional
Armaturefficiëntie	>140lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Attached to the fixture, Loose driver
Energielabel	A++
Family	Myos
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	3000K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	Optioneel
Material	Acrylic, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Multioptic® lenstechnologie
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)

Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Rectangular
Zelfklevende stofkap	Optioneel

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at

<https://atomis.nl/ldt-photometrics/>