



OXO 35 BLACK

Oxo 35 Black is an adjustable recessed spotlight with a 36° lens. This fixture is an elegant miniature recessed spotlight that can be used as both a directional spotlight and a downlight.

- Miniature adjustable spotlight (ø35mm) that can also be pushed up until it sits completely recessed in the ceiling
- Equipped with a 36° FWHM lens
- High color rendering index (CRI>90)>
- On-off version, DALI dimmable and Casambi dimmable versions available

Categories: [Downlights and recessed spotlights](#)



Oxo 35 Black is an adjustable recessed spotlight with a 36° lens. This fixture is an elegant miniature recessed spotlight that can be used as both a directional spotlight and a downlight.

- Miniature adjustable spotlight (ø35mm) that can also be pushed up until it sits completely recessed in the ceiling
- Equipped with a 36° FWHM lens
- High color rendering index (CRI>90)>
- On-off version, DALI dimmable and Casambi dimmable versions available

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
ANSI/IES TM-30-18	Erkend
Armaturefficiëntie	>70lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Loose driver
Energielabel	A++
Family	Oxo
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	N/A
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class-I
Kleurconsistentie (SDCM)	SDCM=2
Kleurtemperatuur	3000K, 4000K
Color Rendering Index (CRI)	CRI97, CRI90, CRI80
Lichtbundel (FWHM)	15°, 17°, 24°, 40°
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Aluminium
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Exhibition spaces, Hospitality, Office, Public spaces, Retail
Self-adhesive dust cover	Optional

Spot bundle (FWHM)	15°, 17°, 24°, 40°
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Round
Zelfklevende stofkap	Optioneel

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at

<https://atomis.nl/ldt-photometrics/>