



## OXO 35 WHITE

Oxo 35 White is an adjustable recessed spotlight with a 36° lens. This fixture is an elegant miniature recessed spotlight that can be used as both a directional spotlight and a recessed downlight.

- Miniature adjustable spotlight (ø35mm) that can also be pushed up until it sits completely recessed in the ceiling
- Equipped with a 36° FWHM lens
- High Color Rendering Index (CRI>90)>
- On-off version, DALI dimmable and Casambi dimmable versions available

### Downloads

[Photometrics Oxo 35 White](#)

**Categories:** [Downlights and recessed spotlights](#)



Oxo 35 White is an adjustable recessed spotlight with a 36° lens. This fixture is an elegant miniature recessed spotlight that can be used as both a directional spotlight and a recessed downlight.

- Miniature adjustable spotlight (ø35mm) that can also be pushed up until it sits completely recessed in the ceiling
- Equipped with a 36° FWHM lens
- High Color Rendering Index (CRI>90)>
- On-off version, DALI dimmable and Casambi dimmable versions available

## Downloads

[Photometrics Oxo 35 White](#)

## NOTES

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Air extraction</b>	N/A
<b>ANSI/IES TM-30-18</b>	Erkend
<b>Armaturefficiëntie</b>	>70lm/W
<b>Bevestiging</b>	Recessed
<b>CIE Flux code</b>	93 100 100 100 100
<b>Driver positie</b>	Loose driver
<b>Energielabel</b>	A++
<b>Family</b>	Oxo
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Glare (UGR)</b>	N/A
<b>IP-class</b>	IP20 (upwards)/IP40 (downwards)
<b>Isolatieklasse</b>	Class-I
<b>Kleurconsistentie (SDCM)</b>	SDCM=2
<b>Kleurtemperatuur</b>	2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI97, CRI90, CRI80
<b>Lichtbundel (FWHM)</b>	15°, 17°, 24°, 40°
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Luchtafzuiging</b>	n.v.t.
<b>Material</b>	Aluminium
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Lens
<b>Oriëntatie</b>	Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
<b>Productkleur</b>	On request
<b>Producttoepassing</b>	Education, Exhibition spaces, Hospitality, Office, Public spaces, Retail
<b>Self-adhesive dust cover</b>	Optional

<b>Spot bundle (FWHM)</b>	15°, 17°, 24°, 40°
<b>Verpakkingsafmetingen</b>	Bulkverpakking
<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)
<b>Voltage / frequentie</b>	220-240V, 50 / 60Hz
<b>Shape</b>	Round
<b>Zelfklevende stofkap</b>	Optioneel

