



[OXO 35 SAPP](#)

Oxo 35 SAPP is an adjustable spotlight with a 36° lens. This elegant miniature spotlight is designed for use within Interlu's SAPP ceiling system.

- Miniature adjustable spotlight (ø35 mm)
- Equipped with a 36° FWHM lens
- High color rendering index (CRI>90)
- On-off version, DALI dimmable and Casambi dimmable versions available

Categories: [Baffle luminaires](#), [Climate ceiling fixtures](#)



PRODUCT IMAGES



Oxo 35 SAPP is an adjustable spotlight with a 36° lens. This elegant miniature spotlight is designed for use within Interlu's SAPP ceiling system.

- Miniature adjustable spotlight (ø35 mm)
- Equipped with a 36° FWHM lens
- High color rendering index (CRI>90)
- On-off version, DALI dimmable and Casambi dimmable versions available

NOTES

ADDITIONAL INFORMATION

Armaturefficiëntie	>70lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Loose driver
Energielabel	A++
Family	Oxo
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	N/A
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=2
Color Rendering Index (CRI)	CRI97, CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Aluminium
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens
Oriëntatie	Adjustable
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Shape	Round
Zelfklevende stofkap	Optioneel

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at

<https://atomis.nl/ldt-photometrics/>