



REFURBISHMENT METRONOME

Refurbishment Metronome is a linear LED fixture featuring a row of 12 lenses decoratively recessed behind a grid-shaped louver. The fixture combines functional lighting with a distinct architectural appearance.

Thanks to the magnetic attachment, installation in ceilings with existing recesses is simple and efficient. This makes Metronome 12 particularly suitable for both renovation projects and new ceiling concepts.

Key features

- Linear LED luminaire
- Row of recessed lenses
- Grid-shaped baffle
- Magnetic attachment
- Easy installation in existing ceiling cutouts
- High efficiency
- Optimal light distribution
- Low glare with UGR less than 19
- Steel housing
- Powder coating
- Custom-made according to client specifications

Categories: [Refurbishment and Retrofit Fixtures](#)



Refurbishment Metronome is a linear LED fixture featuring a row of 12 lenses decoratively recessed behind a grid-shaped louver. The fixture combines functional lighting with a distinct architectural appearance.

Thanks to the magnetic attachment, installation in ceilings with existing recesses is simple and efficient. This makes Metronome 12 particularly suitable for both renovation projects and new ceiling concepts.

Key features

- Linear LED luminaire
- Row of recessed lenses
- Grid-shaped baffle
- Magnetic attachment
- Easy installation in existing ceiling cutouts
- High efficiency
- Optimal light distribution
- Low glare with UGR less than 19
- Steel housing
- Powder coating
- Custom-made according to client specifications

NOTES

ADDITIONAL INFORMATION

Armaturefficiëntie	>140lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Attached to the fixture, Loose driver
Energielabel	A++
Family	Metronome
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	Optioneel
Material	Acrylic, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens en louver
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces, Retail
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Shape	Rectangular

Zelfklevende stofkap

Optioneel

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at
<https://atomis.nl/ldt-photometrics/>