



## **REFURBISHMENT METRONOME**

Refurbishment Metronome is a linear LED fixture featuring a row of 12 lenses decoratively recessed behind a grid-shaped louver. The fixture combines functional lighting with a distinct architectural appearance.

Thanks to the magnetic attachment, installation in ceilings with existing recesses is simple and efficient. This makes Metronome 12 particularly suitable for both renovation projects and new ceiling concepts.

### **Key features**

- Linear LED luminaire
- Row of recessed lenses
- Grid-shaped baffle
- Magnetic attachment
- Easy installation in existing ceiling cutouts
- High efficiency
- Optimal light distribution
- Low glare with UGR less than 19
- Steel housing
- Powder coating
- Custom-made according to client specifications

**Categories:** [Refurbishment and Retrofit Fixtures](#)



Refurbishment Metronome is a linear LED fixture featuring a row of 12 lenses decoratively recessed behind a grid-shaped louver. The fixture combines functional lighting with a distinct architectural appearance.

Thanks to the magnetic attachment, installation in ceilings with existing recesses is simple and efficient. This makes Metronome 12 particularly suitable for both renovation projects and new ceiling concepts.

### **Key features**

- Linear LED luminaire
- Row of recessed lenses
- Grid-shaped baffle
- Magnetic attachment
- Easy installation in existing ceiling cutouts
- High efficiency
- Optimal light distribution
- Low glare with UGR less than 19
- Steel housing
- Powder coating
- Custom-made according to client specifications

## NOTES

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Armaturefficiëntie</b>	>140lm/W
<b>Bevestiging</b>	Recessed
<b>CIE Flux code</b>	93 100 100 100 100
<b>Driver positie</b>	Attached to the fixture, Loose driver
<b>Energielabel</b>	A++
<b>Family</b>	Metronome
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Glare (UGR)</b>	<19
<b>IP-class</b>	IP20 (upwards)/IP40 (downwards)
<b>Isolatieklasse</b>	Class II
<b>Kleurconsistentie (SDCM)</b>	SDCM=3
<b>Kleurtemperatuur</b>	Tunable White, 2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI90, CRI80
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Luchtafzuiging</b>	Optioneel
<b>Material</b>	Acrylic, Steel
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Lens en louver
<b>Oriëntatie</b>	Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
<b>Productkleur</b>	On request
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces, Retail
<b>Self-adhesive dust cover</b>	Optional
<b>Verpakkingsafmetingen</b>	Bulkverpakking
<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)
<b>Shape</b>	Rectangular

**Zelfklevende stofkap**

Optioneel

