



## **SIRIO-SAPP 900**

Sirio-Sapp 900 is a linear lighting fixture with lenses for use in Interlu SAPP® ceilings.

- Sirio SAPP 900 can be placed between the structures, creating an integrated system with the ceiling without interrupting the architectural appearance.
- Provides highly controlled light distribution, excellent uniformity and UGR<19
- The fixture complies with NEN-EN 12464-1

**Categories:** [Baffle luminaires](#), [Climate ceiling fixtures](#)



Sirio-Sapp 900 is a linear lighting fixture with lenses for use in Interalu SAPP® ceilings.

- Sirio SAPP 900 can be placed between the structures, creating an integrated system with the ceiling without interrupting the architectural appearance.
- Provides highly controlled light distribution, excellent uniformity and UGR<19
- The fixture complies with NEN-EN 12464-1

**NOTES**

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Air extraction</b>	N/A
<b>Armaturefficiëntie</b>	>125lm/W
<b>Bevestiging</b>	Recessed
<b>CIE Flux code</b>	93 100 100 100 100
<b>Driver positie</b>	Loose driver
<b>Energielabel</b>	A++
<b>Family</b>	Sirio
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Glare (UGR)</b>	<19
<b>IP-class</b>	IP20 (upwards)/IP40 (downwards)
<b>Isolatieklasse</b>	Class II
<b>Kleurconsistentie (SDCM)</b>	SDCM=3
<b>Kleurtemperatuur</b>	Tunable White, 2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI90, CRI80
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Luchtafzuiging</b>	n.v.t.
<b>Material</b>	Acrylic, Steel
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Lens en louver
<b>Oriëntatie</b>	Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
<b>Productkleur</b>	On request
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces
<b>Self-adhesive dust cover</b>	Optional
<b>Specificaties</b>	G7D1 / 06-02-2025
<b>Verpakkingsafmetingen</b>	Bulkverpakking

<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)
<b>Voltage / frequentie</b>	220-240V, 50 / 60Hz
<b>Shape</b>	Rectangular
<b>Zelfklevende stofkap</b>	Optioneel

## PHOTOMETRIC DATA

17.830 Sirio 900 SAPP 6W 800lm 3000K CRI80 G7d  
17.830 Sirio 900 SAPP 7W 900lm 3000K CRI80 G7d  
17.830 Sirio 900 SAPP 9W 1100lm 3000K CRI80 G7d  
17.830 Sirio 900 SAPP 10W 1300lm 3000K CRI80 G7d  
17.830 Sirio 900 SAPP 12W 1500lm 3000K CRI80 G7d  
17.830 Sirio 900 SAPP 13W 1500lm 3000K CRI80 G7d  
17.830 Sirio 900 SAPP 16W 1900lm 3000K CRI80 G7d  
17.830 Sirio 900 SAPP 18W 2200lm 3000K CRI80 G7d  
17.840 Sirio 900 SAPP 6W 800lm 4000K CRI80 G7d  
17.840 Sirio 900 SAPP 7W 900lm 4000K CRI80 G7d  
17.840 Sirio 900 SAPP 9W 1200lm 4000K CRI80 G7d  
17.840 Sirio 900 SAPP 10W 1300lm 4000K CRI80 G7d  
17.840 Sirio 900 SAPP 12W 1500lm 4000K CRI80 G7d  
17.840 Sirio 900 SAPP 13W 1700lm 4000K CRI80 G7d  
17.840 Sirio 900 SAPP 16W 2000lm 4000K CRI80 G7d  
17.840 Sirio 900 SAPP 18W 2300lm 4000K CRI80 G7d

## LDT / PHOTOMETRICS DOWNLOADS

### LDT / Photometrics downloads

All downloads can be found centrally per family at  
<https://atomis.nl/ldt-photometrics/>