



SIRIO-SAPP 900

A linear lighting fixture with lenses for use in Interalu SAPP® ceilings.

- Sirio SAPP 900 can be placed between the structures, creating an integrated system with the ceiling without interrupting the architectural appearance.
- Provides highly controlled light distribution, excellent uniformity and UGR<19
- The fixture complies with NEN-EN 12464-1

Create your own product, download the PDF specification sheet or add to the quotation:

Categories: [Baffle luminaires](#), [Climate ceiling fixtures](#)



A linear lighting fixture with lenses for use in Interalu SAPP® ceilings.

- Sirio SAPP 900 can be placed between the structures, creating an integrated system with the ceiling without interrupting the architectural appearance.
- Provides highly controlled light distribution, excellent uniformity and UGR<19
- The fixture complies with NEN-EN 12464-1

Create your own product, download the PDF specification sheet or add to the quotation:

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
Armaturefficiëntie	>125lm/W
Bevestiging	Recessed
CIE Flux code	93 100 100 100 100
Driver positie	Loose driver
Energielabel	A++
Family	Sirio
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Acrylic, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Lens en louver
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional
Specificaties	G7D1 / 06-02-2025
Verpakkingsafmetingen	Bulkverpakking

Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Rectangular
Zelfklevende stofkap	Optioneel

PHOTOMETRIC DATA

17.830 Sirio 900 SAPP 6W 800lm 3000K CRI80 G7d
17.830 Sirio 900 SAPP 7W 900lm 3000K CRI80 G7d
17.830 Sirio 900 SAPP 9W 1100lm 3000K CRI80 G7d
17.830 Sirio 900 SAPP 10W 1300lm 3000K CRI80 G7d
17.830 Sirio 900 SAPP 12W 1500lm 3000K CRI80 G7d
17.830 Sirio 900 SAPP 13W 1500lm 3000K CRI80 G7d
17.830 Sirio 900 SAPP 16W 1900lm 3000K CRI80 G7d
17.830 Sirio 900 SAPP 18W 2200lm 3000K CRI80 G7d
17.840 Sirio 900 SAPP 6W 800lm 4000K CRI80 G7d
17.840 Sirio 900 SAPP 7W 900lm 4000K CRI80 G7d
17.840 Sirio 900 SAPP 9W 1200lm 4000K CRI80 G7d
17.840 Sirio 900 SAPP 10W 1300lm 4000K CRI80 G7d
17.840 Sirio 900 SAPP 12W 1500lm 4000K CRI80 G7d
17.840 Sirio 900 SAPP 13W 1700lm 4000K CRI80 G7d
17.840 Sirio 900 SAPP 16W 2000lm 4000K CRI80 G7d
17.840 Sirio 900 SAPP 18W 2300lm 4000K CRI80 G7d