



STRATOS-B 70

Stratos-B 70 is a linear LED luminaire designed for use in climate ceilings with visible bandraster profiles. The fixture is shielded by a micro-prismatic lens (with UGR 19 for office applications according to EN 12464-1).

- Powder-coated aluminum construction
- Equipped with a prismatic lens (UGR 19)
- Tunable white or melanopic lighting versions available
- Suitable for use in offices, schools, care centers and other public facilities.

Downloads

[Photometrics Stratos-B 70](#)

Create your own product, download the PDF specification sheet or add to the quotation:

Categories: [Strip grid fixtures](#)



Stratos-B 70 is a linear LED luminaire designed for use in climate ceilings with visible bandraaster profiles. The fixture is shielded by a micro-prismatic lens (with UGR 19 for office applications according to EN 12464-1).

- Powder-coated aluminum construction
- Equipped with a prismatic lens (UGR 19)
- Tunable white or melanopic lighting versions available
- Suitable for use in offices, schools, care centers and other public facilities.

Downloads

[Photometrics Stratos-B 70](#)

Create your own product, download the PDF specification sheet or add to the quotation:

NOTES

ADDITIONAL INFORMATION

Air extraction	Optional
Armaturefficiëntie	>140lm/W
Bevestiging	Recessed
Breedte	70mm
CIE Flux code	93 100 100 100 100
Driver positie	Attached to the fixture, Loose driver
Energielabel	A++
Family	Stratos
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Length	1720mm
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	Optioneel
Material	Acrylic, Aluminium
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Microprismatic lens, Opalen diffusor
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	Optional

Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz
Shape	Rectangular
Zelfklevende stofkap	Optioneel

