



## INTERLINE-SAPP

### SEAMLESS LINEAR LIGHTING FOR INTERALU SAPP — SLEEK, FLEXIBLE AND COMFORTABLE (UGR<19).

Atolux Interline SAPP is a minimalist and elegant linear luminaire that integrates seamlessly into the Interalu SAPP slatted ceiling. Thanks to the smart clamping spring mechanism the luminaire simply clicks into the joint—quick to install and effortless to reposition if the room layout changes.

The combination of sleek design and high-quality optics ensures a pleasant, calm light distribution. The matte black optics provide a comfortable visual experience with UGR < 19, ideal for workstations and modern office environments.

With an efficiency of >130 lm/W and a high CRI 90, Interline SAPP combines maximum light output with natural color rendering—perfect for high-quality task lighting according to EN 12464-1 for office applications.

It is also practical: the luminaire comes standard with a DALI-2 driver, including a 5-meter connection cable between driver and luminaire and a GST18i5 male/female compatible connection on the driver for fast, error-free installation and daisy-chaining.

Available in white or black coating, ensuring the luminaire always matches the ceiling and interior concept.

Dimensions:

W21xL850

W21xL1130

W21xL1410

**Create your own product, download the PDF specification sheet or add to the quotation:**

Categories: [Baffle luminaires](#), [Climate ceiling fixtures](#)



## **SEAMLESS LINEAR LIGHTING FOR INTERALU SAPP — SLEEK, FLEXIBLE AND COMFORTABLE (UGR<19).**

Atolux Interline SAPP is a minimalist and elegant linear luminaire that integrates seamlessly into the Interalu SAPP slatted ceiling. Thanks to the smart clamping spring mechanism the luminaire simply clicks into the joint—quick to install and effortless to reposition if the room layout changes.

The combination of sleek design and high-quality optics ensures a pleasant, calm light distribution. The matte black optics provide a comfortable visual experience with UGR < 19, ideal for workstations and modern office environments. With an efficiency of >130 lm/W and a high CRI 90, Interline SAPP combines maximum light output with natural color rendering—perfect for high-quality task lighting according to EN 12464-1 for office applications.

It is also practical: the luminaire comes standard with a DALI-2 driver, including a 5-meter connection cable between driver and luminaire and a GST18i5 male/female compatible connection on the driver for fast, error-free installation and daisy-chaining.

Available in white or black coating, ensuring the luminaire always matches the ceiling and interior concept.

### Dimensions:

W21xL850

W21xL1130

W21xL1410

**Create your own product, download the PDF specification sheet or add to the quotation:**

**NOTES**

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Armaturefficiëntie</b>	>130lm/W
<b>Color Rendering Index (CRI)</b>	CRI90
<b>Glare (UGR)</b>	<19
<b>Kleurtemperatuur</b>	2700K, 3000K, 4000K
<b>Luchtafzuiging</b>	n.v.t.
<b>Bevestiging</b>	Recessed
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>IP-class</b>	IP20 (upwards)/IP40 (downwards)
<b>Isolatieklasse</b>	Class II
<b>Kleurconsistentie (SDCM)</b>	SDCM=3
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Lens en louver
<b>Oriëntatie</b>	Down
<b>Verpakkingsafmetingen</b>	Bulkverpakking
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces
<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)
<b>Shape</b>	Rectangular

