



## **ZENDER**

Zender, a wall-mounted LED fixture, is designed for architectural indoor lighting of vertical surfaces such as walls, corridors and stairs. Light emitted by an internally mounted LED strip directed toward the wall is first diffused by a double frosted diffuser and then reflected upward and downward, creating a softly illuminated wall.

- Robust design fixture for wall mounting suitable for corridors and entrance halls in public spaces of schools, etc.
- Available in 300 mm wide and 600 mm wide sizes
- Emergency versions available
- Can be mounted horizontally and vertically

### **Downloads**

[Photometrics Zender BIM files Zender](#)

**Categories:** [Surface-mounted luminaires](#)



## PRODUCT IMAGES



Zender, a wall-mounted LED fixture, is designed for architectural indoor lighting of vertical surfaces such as walls, corridors and stairs. Light emitted by an internally mounted LED strip directed toward the wall is first diffused by a double frosted diffuser and then reflected upward and downward, creating a softly illuminated wall.

- Robust design fixture for wall mounting suitable for corridors and entrance halls in public spaces of schools, etc.
- Available in 300 mm wide and 600 mm wide sizes
- Emergency versions available
- Can be mounted horizontally and vertically

### Downloads

[Photometrics Zender](#) [BIM files Zender](#)

## NOTES

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Air extraction</b>	N/A
<b>Armaturefficiëntie</b>	>100lm/W
<b>Bevestiging</b>	wall mounted
<b>CIE Flux code</b>	93 100 100 100 100
<b>Driver positie</b>	Integrated
<b>Energielabel</b>	A++
<b>Family</b>	Zender
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Glare (UGR)</b>	N/A
<b>IP-class</b>	IP20 (upwards)/IP40 (downwards)
<b>Isolatieklasse</b>	Class-I
<b>Kleurconsistentie (SDCM)</b>	SDCM=3
<b>Kleurtemperatuur</b>	Tunable White, 2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI90, CRI80
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Luchtafzuiging</b>	n.v.t.
<b>Material</b>	Acrylic, Steel
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Opalen diffusor
<b>Oriëntatie</b>	Up+Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	On request, On the driver
<b>Productkleur</b>	On request
<b>Producttoepassing</b>	Education, Exhibition spaces, Hospitality, Office, Public spaces, Retail
<b>Self-adhesive dust cover</b>	Optional
<b>Verpakkingsafmetingen</b>	Bulkverpakking
<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)
<b>Voltage / frequentie</b>	220-240V, 50 / 60Hz

**Shape**

Rectangular

**Zelfklevende stofkap**

Optioneel

## PHOTOMETRIC DATA

Zender 300 10W 950lm 3000K CRI80  
Zender 300 10W 1000lm 4000K CRI80  
Zender 600 19W 1900lm 3000K CRI80  
Zender 600 19W 2050lm 4000K CRI80