



ZENDER

Zender, a wall-mounted LED fixture, is designed for architectural indoor lighting of vertical surfaces such as walls, corridors and stairs. Light emitted by an internally mounted LED strip directed toward the wall is first diffused by a double frosted diffuser and then reflected upward and downward, creating a softly illuminated wall.

- Robust design fixture for wall mounting suitable for corridors and entrance halls in public spaces of schools, etc.
- Available in 300 mm wide and 600 mm wide sizes
- Emergency versions available
- Can be mounted horizontally and vertically

Categories: [Surface-mounted luminaires](#)



PRODUCT IMAGES



Zender, a wall-mounted LED fixture, is designed for architectural indoor lighting of vertical surfaces such as walls, corridors and stairs. Light emitted by an internally mounted LED strip directed toward the wall is first diffused by a double frosted diffuser and then reflected upward and downward, creating a softly illuminated wall.

- Robust design fixture for wall mounting suitable for corridors and entrance halls in public spaces of schools, etc.
- Available in 300 mm wide and 600 mm wide sizes
- Emergency versions available
- Can be mounted horizontally and vertically

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
Armaturefficiëntie	>100lm/W
Bevestiging	wall mounted
CIE Flux code	93 100 100 100 100
Driver positie	Integrated
Energielabel	A++
Family	Zender
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	N/A
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class-I
Kleurconsistentie (SDCM)	SDCM=3
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Acrylic, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Opalen diffusor
Oriëntatie	Up+Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	On request, On the driver
Productkleur	On request
Producttoepassing	Education, Exhibition spaces, Hospitality, Office, Public spaces, Retail
Self-adhesive dust cover	Optional
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz

Shape	Rectangular
Zelfklevende stofkap	Optioneel

PHOTOMETRIC DATA

Zender 300 10W 950lm 3000K CRI80

Zender 300 10W 1000lm 4000K CRI80

Zender 600 19W 1900lm 3000K CRI80

Zender 600 19W 2050lm 4000K CRI80

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at
<https://atomis.nl/ldt-photometrics/>