

ZUMO 60 VARIO BLACK

Zumo 60 Vario is a zoomable LED spotlight for standard 3-phase track systems. The spotlight features a powerful LED with a high color rendering index (CRI> 97). The light beam can be continuously adjusted from 10° spot to 50° wide flood by simply rotating the zoom lens. Zumo 60 Vario spotlights are particularly suitable for lighting galleries, museums and art exhibitions.

- Compact design LED spotlight (ø60mm) for standard track systems
- High CRI (> 97) color rendering index
- Continuously adjustable light beam from 10° spot to 50° wide flood
- Flicker-free dimming (according to IEEE 1789) by dimming on the spotlight
- Particularly suitable for lighting galleries, museums and exhibition spaces








Downloads



[Photometrics Nano 35](#)

Categories: [Track luminaires](#)



PRODUCT IMAGES





Zumo 60 Vario is a zoomable LED spotlight for standard 3-phase track systems. The spotlight features a powerful LED with a high color rendering index (CRI> 97). The light beam can be continuously adjusted from 10° spot to 50° wide flood by simply rotating the zoom lens. Zumo 60 Vario spotlights are particularly suitable for lighting galleries, museums and art exhibitions.

- Compact design LED spotlight (ø60mm) for standard track systems
- High CRI (> 97) color rendering index
- Continuously adjustable light beam from 10° spot to 50° wide flood
- Flicker-free dimming (according to IEEE 1789) by dimming on the spotlight
- Particularly suitable for lighting galleries, museums and exhibition spaces

Downloads

[Photometrics Nano 35](#)

NOTES

ADDITIONAL INFORMATION

Isolatieklasse	Class-I
Producttoepassing	Education, Exhibition spaces, Hospitality, Office, Public spaces, Retail
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Packaging dimensions	Bulk packaging
Bevestiging	Rail
Glare (UGR)	Not applicable
Color Rendering Index (CRI)	CRI97
Light control	1-10V dimming, Casambi dimming, DALI dimming
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Primaire aansluitingen	Fase track
Productkleur	On request
Self-adhesive dust cover	Optional
Air extraction	N/A
Family	Zumo
Oriëntatie	Adjustable
Armatuurefficiëntie	>85lm/W
Driver positie	Integrated
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Ambient temperature	-20°C / +40°C
Optics	Zoom lens
Shape	Round
Spot bundle (FWHM)	10° – 50°
Photobiological safety	IEC 62471: RG1 (low risc)
ANSI/IES TM-30-18	Erkend

