



## **ZUMO 90 VARIO WHITE**

Zumo 90 Vario is a zoomable LED spot for standard 3-phase tracks. The spotlight features a powerful LED with a high color rendering index (CRI> 97). The light beam can be continuously adjusted from 12° spot to 55° wide flood by simply rotating the zoom lens. Zumo 90 Vario spotlights are particularly suitable for illuminating galleries, museums, and art exhibitions.

- Can be used on standard high-voltage tracks
- High CRI (> 97) color rendering index
- Continuously adjustable light beam from 12° spot to 55° wide flood
- Strobe-free dimming ( according to IEEE 1789) + on-site dimming
- Particularly suitable for lighting galleries, museums and exhibition spaces






### **Downloads**

[Photometrics Zumo 90 Vario](#)

**Categories:** [Track luminaires](#)



## PRODUCT IMAGES





Zumo 90 Vario is a zoomable LED spot for standard 3-phase tracks. The spotlight features a powerful LED with a high color rendering index (CRI> 97). The light beam can be continuously adjusted from 12° spot to 55° wide flood by simply rotating the zoom lens. Zumo 90 Vario spotlights are particularly suitable for illuminating galleries, museums, and art exhibitions.

- Can be used on standard high-voltage tracks
- High CRI (> 97) color rendering index
- Continuously adjustable light beam from 12° spot to 55° wide flood
- Strobe-free dimming ( according to IEEE 1789) + on-site dimming
- Particularly suitable for lighting galleries, museums and exhibition spaces

## Downloads

[Photometrics Zumo 90 Vario](#)

## **NOTES**

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Isolatieklasse</b>	Class-I
<b>Producttoepassing</b>	Education, Exhibition spaces, Hospitality, Office, Public spaces, Retail
<b>Kleurtemperatuur</b>	Tunable White, 2700K, 3000K, 3500K, 4000K
<b>Material</b>	Aluminium
<b>Packaging dimensions</b>	Bulk packaging
<b>Bevestiging</b>	Rail
<b>Glare (UGR)</b>	Not applicable
<b>Color Rendering Index (CRI)</b>	CRI97
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Primaire aansluitingen</b>	Fase track
<b>Productkleur</b>	On request
<b>Self-adhesive dust cover</b>	Optional
<b>Air extraction</b>	N/A
<b>Family</b>	Zumo
<b>Armatuurefficiëntie</b>	>100lm/W
<b>Driver positie</b>	Integrated
<b>Verwachte levensduur</b>	L90B50@60,000h (Tq 25°C)
<b>Ambient temperature</b>	-20°C / +40°C
<b>Optics</b>	Zoom lens
<b>Oriëntatie</b>	Adjustable
<b>Shape</b>	Round
<b>Spot bundle (FWHM)</b>	10° – 50°
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>ANSI/IES TM-30-18</b>	Erkend

